

预制连接器的Profinet电缆, 4芯, 屏蔽
Profinet cable with prefabricated connector, 4 core, shielded

45R 型

RJ45, IP20插头

RJ45, IP20弯头插头

RJ45, IP67插头



	RPB	RPBR	RPRD
OE 	PN-RPB-OE-45R/L00XX 31044000XX	PN-RPBR-OE-45R/L00XX 31044100XX	PN-RPRD-OE-45R/L00XX 31043000XX
RPB 	PN-RPB-RPB-45R/L00XX 31049500XX	PN-RPBR-RPB-45R/L00XX 31042100XX	PN-RPRD-RPB-45R/L00XX 31041300XX
RPBR 		PN-RPBR-RPBR-45R/L00XX 31042200XX	
RPRD 			PN-RPRD-RPRD-45R/L00XX 31043300XX
MSD 			
MRD 			
FSDBP 	PN-RPB-FSDBP-45R/L00XX 31041900XX		

此页匹配线缆参数



类型: 45R
 护套: PUR
 结构: 22AWG*4C 导体19根束绞
 安装: 适用于机械手
 温度: -20 °C ... 80 °C

M12针式, 直头

M12针式, 弯头

M12孔式, 直头

M12孔式, 弯头



MSD

MRD

FSD

FRD

PN-MSD-OE-45R/L00XX 31045000XX	PN-MRD-OE-45R/L00XX 31046000XX	PN-FSD-OE-45R/L00XX 31047000XX	PN-FRD-OE-45R/L00XX 31048000XX
PN-MSD-RPB-45R/L00XX 31045100XX	PN-MRD-RPB-45R/L00XX 31046100XX	PN-FSD-RPB-45R/L00XX 31047100XX	PN-FRD-RPB-45R/L00XX 31048100XX
PN-MSD-RPBR-45R/L00XX 31045200XX	PN-MRD-RPBR-45R/L00XX 31046200XX	PN-FSD-RPBR-45R/L00XX 31047200XX	PN-FRD-RPBR-45R/L00XX 31048200XX
PN-MSD-RPRD-45R/L00XX 31045300XX	PN-MRD-RPRD-45R/L00XX 31046300XX	PN-FSD-RPRD-45R/L00XX 31047300XX	PN-FRD-RPRD-45R/L00XX 31048300XX
PN-MSD-MSD-45R/L00XX 31045500XX	PN-MRD-MSD-45R/L00XX 31045600XX	PN-FSD-MSD-45R/L00XX 31045700XX	PN-FRD-MSD-45R/L00XX 31045800XX
	PN-MRD-MRD-45R/L00XX 31046600XX	PN-FSD-MRD-45R/L00XX 31046700XX	PN-FRD-MRD-45R/L00XX 31046800XX

订购方式 (长度定制示例)



注: 以10厘米为刻度
例: L0010=1米

信号指示、线路分配

M12	RJ45	线芯颜色	信号
1	1	黄色	TD+
3	2	橙色	TD-
2	3	白色	RD+
4	6	蓝色	RD-




预制连接器的Profinet电缆, 4芯, 屏蔽
Profinet cable with prefabricated connector, 4 core, shielded

45R 型

M12针式, 金属直头

M12孔式, 金属直头



	SD4A5	SD4C5
 RPB	PN-RPB-SD4A5-45R/L00XX 31045900XX	PN-RPB-SD4C5-45R/L00XX 31046900XX
 RPDB4	PN-SD4A5-RPDB4-45R/L00XX 31040200XX	PN-SD4C5-RPDB4-45R/L00XX 31040500XX
 SD4A5	PN-SD4A5-SD4A5-45R/L00XX 31040300XX	PN-SD4A5-SD4C5-45R/L00XX 31049900XX

此页匹配线缆参数



类型: 45R
护套: PUR
结构: 22AWG*4C 导体19根束绞
安装: 适用于机械手臂
温度: -20 °C ... 80 °C

订购方式 (长度定制示例)



注: 以10厘米为刻度
例: L0010=1米

信号指示、线路分配

M12	RJ45	线芯颜色	信号
1	1	黄色	TD+
3	2	橙色	TD-
2	3	白色	RD+
4	6	蓝色	RD-