

预制连接器的以太网电缆, 8芯, 屏蔽, CAT6_A
Ethernet cable with prefabricated connector, 8 core, shielded, CAT6_A

48P 型

RJ45, IP20插头

RJ45, IP20插头

M12针式, 直头, X编码

Ethernet



EtherNet/IP



	RPC	RPD	MSX
OE	EH6-RPC-OE-48P/L00XX 31192000XX	EH6-RPD-OE-48P/L00XX 31191000XX	EH6-MSX-OE-48P/L00XX 31195000XX
RPC	EH6-RPC-RPC-48P/L00XX 31191100XX		EH6-MSX-RPC-48P/L00XX 31195100XX
RPD		EH6-RPD-RPD-48P/L00XX 31192100XX	EH6-MSX-RPD-48P/L00XX 31195400XX
RPRC		EH6-RPD-RPRC-48P/L00XX 31191300XX	EH6-MSX-RPRC-48P/L00XX 31195300XX
MSX			EH6-MSX-MSX-48P/L00XX 31195500XX

此页匹配线缆参数



类型: 48P
护套: PUR
结构: 26AWG*4P 导体7根束绞
安装: 适用于活动安装或拖链安装
温度: -20 °C ... 80 °C

订购方式 (长度定制示例)



注: 以10厘米为刻度
例: L0010=1米

信号指示、线路分配

M12	RJ45	线芯颜色	信号
1	1	白色橙色	D1+
2	2	橙色	D1-
7	5	白色蓝色	D3+
8	4	蓝色	D3-
3	3	白色绿色	D2+
4	6	绿色	D2-
5	7	白色棕色	D4+
6	8	棕色	D4-