


电磁阀, 插座, 注塑成型式, A型  
Valve plug, molded cable, Type A



技术参数/Technical data


|                              |   |
|------------------------------|---|
| 执行标准/Standard                | DIN EN 175 301-803-A  |
| 适用温度/Ambient temperature     | -40°C ~ +80°C(静态温度/fixed installation)<br>-20°C ~ +80°C(动态温度/flexible installation) |
| 端子类型/Termination             | 焊接型/Soldering   |
| 端子尺寸/Pin dimensions          | 6.3x0.8mm, 4.8x0.8mm  |
| 外模材料/Connector overmold      | TPU   |
| 外壳材料/Sheating material       | PA+GF   |
| 胶芯材料/Connector insert        | PC  |
| 端子材料/Connector contacts      | 磷青铜镀银/PS with silver plated   |
| 螺丝材料/Screw                   | 钢镀锌/Steel with Zn plated  |
| 密封材料/Seal                    | 氟橡胶(FMK)  |
| 垫片材料/Gasket                  | TPU/丁晴橡胶(NBR)   |
| 额定电压/Rated voltage           | 24V/250V  |
| 额定脉冲电压/Rated impulse voltage | 800V/4000V  |
| 额定电流/Rated current           | 8A/10A  |
| 绝缘阻抗/Insulation resistance   | ≥100MΩ  |
| 接触阻抗/Contact resistance      | ≤4mΩ  |
| 防护等级/IP rating               | IP 67(锁紧状态/in locked condition)   |
| 线材类型 /Cable type             | PVC/PUR外被/Cable   |
| 导体规格/Conductor size          | max.1.5mm <sup>2</sup>  |

订货信息/Ordering information

| 芯数/Contacts |  | 型号/Model     |
|-------------|--|--------------|
| 3+PE        |  | VA31-01-XX/V |
| 2+2PE       |  | VA22-01-XX/V |
| 2+PE        |  | VA21-01-XX/V |
| 3P          |  | VA30-01-XX/V |
| 4P          |  | VA40-01-XX/V |

| 常规线路图/Normal circuit diagram      |  |
|-----------------------------------|--|
|                                   |  |
|                                   |  |
| 可定制线路图/Customized circuit diagram |  |

电磁阀, 插座, 注塑成型式, B型  
Valve plug, molded cable, Type B



技术参数/Technical data

|                              |   |
|------------------------------|---|
| 执行标准/Standard                | 工业标准/Industrial standard  |
| 适用温度/Ambient temperature     | -40°C ~ +80°C(静态温度/fixed installation)<br>-20°C ~ +80°C(动态温度/flexible installation) |
| 端子类型/Termination             | 焊接型/Soldering   |
| 端子尺寸/Pin dimensions          | 6.3x0.8mm,4.8x0.8mm   |
| 外模材料/Connector overmold      | TPU   |
| 外壳材料/Sheating material       | PA+GF   |
| 胶芯材料/Connector insert        | PC  |
| 端子材料/Connector contacts      | 磷青铜镀银/PS with silver plated   |
| 螺丝材料/Screw                   | 钢镀锌/Steel with Zn plated  |
| 密封材料/Seal                    | 氟橡胶(FMK)  |
| 垫片材料/Gasket                  | TPU/丁晴橡胶(NBR)   |
| 额定电压/Rated voltage           | 24V/250V  |
| 额定脉冲电压/Rated impulse voltage | 800V/4000V  |
| 额定电流/Rated current           | 8A/10A  |
| 绝缘阻抗/Insulation resistance   | ≥100MΩ  |
| 接触阻抗/Contact resistance      | ≤4mΩ  |
| 防护等级/IP rating               | IP 67(锁紧状态/in locked condition)   |
| 线材类型 /Cable type             | PVC/PUR外被/Cable   |
| 导体规格/Conductor size          | Max.1.5mm <sup>2</sup>  |

订货信息/Ordering information

| 芯数/Contacts | 型号/Model      |
|-------------|---------------|
| 2+PE        | VBI21-01-XX/V |

常规线路图/Normal circuit diagram

01

可定制线路图/Customized circuit diagram

